

Contact-less Credentials EM & MF Series

EM 4100 ISO

125 kHz EM ISO card, thin flexible polyvinyl chloride (PVC) laminate, passive and preprogrammed with a 34 bit card number. The card size is 86 x 54 x 0.84 mm. The card is white with the TRIMEC logo and card number on one side and the other side is blank for customer printing.



MF 550 Clamshell

13.56MHz MIFARE Clamshell card, 1Kbyte, passive and preprogrammed with 34 bit CSN. The card size is 86 X 54 X 1.8 mm. The card is white with the TRIMEC logo and card number on one side. No customer printing is available on the clamshell card.

EM 4100 Clamshell

125 kHz EM Clamshell card, passive and preprogrammed with a 34 bit card number. The card size is 86 x 54 x 1.8 mm. The card is white with the TRIMEC logo and card number on one side. No customer printing is available on the clamshell card.

MF 570 ISO

13.56MHz MIFARE ISO card, 4Kbyte, thin flexible polyvinyl chloride (PVC) laminate, passive and preprogrammed with a 34 bit card number. The card size is 86 x 54 x 0.84 mm. The card is white with the TRIMEC logo and card number on one side and the other side is blank for customer printing.

MF 550 ISO

13.56MHz MIFARE ISO card, 1 Kbyte, thin flexible polyvinyl chloride (PVC) laminate, passive and preprogrammed with a 34 bit card number. The card size is 86 x 54 x 0.84 mm. The card is white with the TRIMEC logo and card number on one side and the other side is blank for customer printing.

Door Release Button



Rated Through Current : 5Q
 Rated Voltage Applied : 230V, AC
 Materials : Aluminium
 Humidity : 95%
 Weight : 150g
 Working Temp : -20° +50°
 Available Size:
 • Slimline Mullion (87 x 50 x 30 mm)
 • Standart Asian Box (87 x 87 x 30 mm)



PLASTIC PUSH BUTTON

Rated Through Current : 5Q
 Rated Voltage Applied : 230V, AC
 Materials : Aluminium
 Humidity : 95%
 Weight : 150g
 Working Temp : -20° +50°
 Available Size:
 • Slimline Mullion (87 x 50 x 30 mm)
 • Standart Asian Box (87 x 87 x 30 mm)



Rated Through Current : 5Q
 Rated Voltage Applied : 230V, AC
 Materials : Stainless Steel
 Humidity : 95%
 Weight : 150g
 Working Temp : -20° +50°
 Available Size:
 • Slimline Mullion (87 x 50 x 30 mm)
 • Standart Asian Box (87 x 87 x 30 mm)

Break Glass



ENGLISH-CHINESE VERSION

Rated Through Current : 8.0A
 Rated Voltage Applied : 250 VAC-12VAC
 Alarm Output : NC, NO
 Humidity : 95%
 Weight : 200g
 Working Temp : -20° +50°
 Color : Green or White
 Installation : Flush or Surface
 Dimensions : 87 x 87 x 51 mm



ENGLISH VERSION

Rated Through Current : 8.0A
 Rated Voltage Applied : 250 VAC-12VAC
 Alarm Output : NC, NO
 Humidity : 95%
 Weight : 200g
 Working Temp : -20° +50°
 Color : Green or White
 Installation : Flush or Surface
 Dimensions : 87 x 87 x 51 mm

Distributed by:

TRIMEC
 ASSA ABLOY